

In the Claims

Applicant has submitted a new complete claim set indicating marked-up claims with insertions and deletions indicated by underlining and strikeouts, respectively.

1. (Currently amended) A driver circuit connected to a supply voltage for driving a line in a network comprising:

first driving means for driving the line, said first driving means comprising a plurality of current sources arranged in a bridge configuration;

second driving means for driving the line; and

at least one control signal for selecting between the first and second driving means; and

a plurality of terminating elements coupled to an output of the driver circuit;

wherein the ~~driver circuit operates~~first and second driving means are operated to limit a voltage at the output to about one-half of the supply voltage.

2. (Previously amended) The driver circuit of claim 1, wherein the at least one control signal operates to make only one of said first or second driving means active at any one time.

3. (Currently amended) The driver circuit of claim 1, wherein the at least one control signal comprises:

a first logic control input signal for enabling and disabling the first driving means; and

~~a logical complement of the logic~~second control signal for enabling and disabling the second driving means;

wherein, when one of the first or second driving means is enabled, the other driving means is disabled.

4-6. (Cancelled).

7. (Original) The driver circuit of claim 1, wherein the second driving means comprises a voltage source.

8. (Previously amended) A driver circuit for driving lines in a network comprising:
a plurality of current sources connected in a bridge configuration and coupled to said lines to provide a bridge current driver;
a voltage source coupled to said lines to provide a voltage driver;
a plurality of terminating elements coupled to the current sources, the voltage source, and to said lines;
supply voltages coupled to the bridge current driver and the voltage driver, wherein the supply voltages include a mid-point termination voltage;
at least one control signal for selecting between the bridge current driver and the voltage driver, such that, when the bridge current driver is selected, the terminating elements are coupled to the mid-point termination voltage, and the lines are driven from the bridge current driver; and
when the voltage driver is selected, the bridge current driver is disabled and the terminating elements are coupled to the voltage driver.
9. (Original) The driver circuit of claim 8, wherein the mid-point termination voltage is approximately equal to one-half the supply voltage.
10. (Original) The driver circuit of claim 8, wherein the terminating elements comprise a network of resistors.
11. (Previously amended) A line driver circuit comprising:
a current source coupled to a first pair of terminals of a termination network, the current source comprising a plurality of current sources arranged in a bridge configuration; and
a voltage source coupled to a second pair of terminals of the termination network;
wherein the line driver circuit operates in a first configuration to establish a first mode of operation, and in a second configuration to establish a second mode of operation, wherein the second mode of operation comprises a current source drive mode wherein the first pair of terminals of the termination network are driven with the current sources while the voltage source

maintains the second pair of terminals of the termination network at a predetermined, non-zero potential comprising one-half of line driver circuit supply voltage.

12-13. (Cancelled).

14. (Original) The line driver circuit in accordance with claim 11, wherein the first mode of operation comprises voltage source drive mode.

15. (Original) The line driver circuit in accordance with claim 14, wherein the first configuration of the line driver circuit corresponding to voltage source drive mode comprises driving the second pair of terminals of the termination network with the voltage source while the current source is maintained in an OFF state.

16-18. (Cancelled).

19. (Original) The line driver circuit in accordance with claim 11, wherein the termination network comprises a resistive termination network.

20. (Original) The line driver circuit in accordance with claim 19, wherein the resistive termination network comprises a pair of resistors with the voltage source outputs coupled to a first end of each resistor and the current source outputs coupled to a second end of each resistor.

21. (Previously amended) A method for providing multi-mode driver capability, the method comprising the steps of:

- (a) providing a line driver circuit including both a current source and a voltage source;
- (b) selecting a first or second mode of operation;
- (c) operating the line driver circuit in a first configuration when the first mode of operation is selected;

(d) operating the line driver circuit in a second configuration when the second mode of operation is selected; and

(e) limiting the output voltage to about one-half of a supply voltage for the driver circuit.